

:

KL I

•

•

•

•

I M F E K F I P

SCT CONFIDENTIAL

SCT CONF



I FDD E FG I KE FE KFE

4 6 1) 8) 6	() -2-8- 2	1 -2	1	2-8







I KE



4 6 1) 8) 6	() -2-8- 2	1 -2	1	2-8

SCT CONFIDENTIAL

SCTC

KPG C I K I K



KPG C I K I K



SCT Co

FG I KFE

0

= $\frac{\times}{\quad}$

•
•

= $\frac{x}{-}$

•
•
•


≥ $\frac{- ()}{- ()}$

•
•



()

1


SCTCO




SCT CONFIDENTIAL



1 - 4












(4	) :

SCT CONFIDENTIAL

SCT Co


SCT CONFIDENTIAL






SCT Co

G B E F I D K F E




2 8)

K G E I C E FID KFE




PRODUCT SPECIFICATIONS					
TYPE WIDTH	ϕA	ϕN	W1(mm)	W2(mm)	W3(mm)
16MM	330 ± 2.0	100 ± 1.0	16.4	22.4	15.9/19.4



tolerance ± 0.2
 100mm.
 measured on a plane 0.3mm above the bottom of the
 d from a plane on the inside bottom of the pocket to
 ie of the carrier.
 ion relative to sprocket hole measured as true position
 t pocket hole.
 er and pocket hole center must be same position.

NOTES:
 1.10 sprocket hole pitch cumulat
 2.Camber not to exceed 1mm in
 3.Material: Black conductive Polys
 4.A and Be
 5.ko-measure
 6-Pocket post
 7.Pocket cent

PIN1



User Direction of Feed